

A

B

C

D

CEDULA DE EQUIPO FAN-COILS CLINICA TODOS SOMOS MEXICANOS																									
SIMBOLO	MODELO	MARCA	CFM SA	TONELADA	CONDICIONES DE CARGA DE ENFRIAMIENTO										CONDICIONES DE CARGA DE CALEFACCION						EXT. CP. IN WC.	MOTOR HP	VOLTS	FASES	CICLOS HZ.
					Qc(KBTU/HR)	Qc(KBTU/HR)	GPM	EAT(°F)		LAT(°F)		H2O TEMP		Qh(KBTU/HR)	GPM	EAT(°F)	LAT(°F)	H2O TEMP							
								DB	WB	DB	WB	ENT	LVG					ENT	LVG						
FC-3	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-4	BCHB91	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-5	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1.0	120	1	60	
FC-6	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-7	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-8	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-10	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-11	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-13	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-17	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-18	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-19	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-22	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-23	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-25	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1	120	1	60	
FC-26A	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1	120	1	60	
FC-26B	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1	120	1	60	
FC-27	BCHB90	TRANE	3600	6	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-28	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-29	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-30	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-31	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-32	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-33	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-34	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-35	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-43	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-44	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-45	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-46	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3	0.2	70	82	180	150	0.36	3/4	120	1	60	
FC-47	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-48A	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-48B	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2	120	1	60	
FC-68	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-69	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-70	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1.0	120	1	60	
FC-71	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-72	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-73	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-74	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-76A	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-76B	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-76C	BCHB90	TRANE	3600	9	58.7	57.3	7.83	70	58	56	53	40	55	32.3	2.15	70	82	180	150	0.35	2.0	120	1	60	
FC-77	BCHB54	TRANE	2400	6	39.2	38.2	5.22	70	58	56	53	40	55	21.5	1.43	70	82	180	150	0.33	1.0	120	1	60	
FC-78	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-79	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-80	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-81	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-82	BCHB36	TRANE	1535	3.8	25.1	24.4	3.85	70	58	56	53	40	55	10.4	0.69	70	82	180	150	0.30	3/4	120	1	60	
FC-83	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-84	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-85	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-86	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82	180	150	0.36	3/4	120	1	60	
FC-87	FCCB080	TRANE	670	1.6	12.5	10.7	1.67	70	58	56	53	40	55	3.0	0.20	70	82								